



ROSETTA

ROSETTA
Espresso, from a new perspective



Elegance meets sophistication

Welcome to the Rosetta range, built to be elegant and solid, with sophisticated design detail that draws attention to them. Offering several models in the range, ensures that you will always be able to match a model to the right requirements.

You can be sure that all Rosetta machines deliver what they promise. We have combined our genuine experience of building first-class espresso machines with creative solutions and the latest innovative technology.

Perfectly brewed espresso, and steaming hot cappuccinos to please your guests, every day, year after year. Rosetta fits in all types of environments, from small artisan coffee shops to top-level restaurants..



Features

- Built in volumetric pump equipped with 2 stage retention and solid particle filtration
- Copper boiler incorporating both pressure relief and anti-vacuum valves
- Boiler drain tap (except compact)
- Group heads with direct pre-infusion chamber
- Decorative stainless cup rail
- Cool wall stainless steam arms
- Electronic hot water controlled outlet

Control

- PID Control
- Heating element thermal cut off
- Automatic back flush program
- 4 program doses settings
- Grind quality alarms
- Service period notification
- Water filter change alarm

Display Features

- Advertising display
- Coffee usage audit
- Daily machine on/off program
- Digital boiler temperature control
- Precision PID control

Standard supplied accessories

- 1 single filter handle all machines
- 2 group machine, 2 double filter handles
- 3 group machine, 3 double filter handles
- Espresso cup stands
- 1.5 metre waste connection hose
- 0.55 metre filter connection hose
- 1 cleaning membrane



Filled with technology



Variants



Compact 2 Group



2 Group



3 Group

Specifications	2 group compact	2 group	3 group three phase
Height	20.86 in / 530mm	20.86 in / 530mm	20.86 in / 530mm
Depth	23.22 in / 590mm	23.22 in / 590mm	23.22 in / 590mm
Width	18.11 in / 460mm	26.77 in / 680mm	38.58 in / 980mm
Weight	88 lb / 40 kg	121 lb / 55 kg	160 lb / 73 kg
Brewing Groups	2	2	3
Boiler Volume (Litre)	6	11.5	17.5
Boiler Pressure (Bar)	0.8 to 1.2	0.8 to 1.2	0.8 to 1.2
Total Boilers	1	1	1
Steam Wands	1	2	2
Hot Water Tap	1	1	1
Noise Level	<70dB	<70dB	<70dB
Power supply	220-240VAC, 50/60Hz, 1N-2780W	220-240VAC, 50/60Hz, 1N-3330W	380-415VAC, 50/60Hz, 3N-6290W
Water connection	G3/8 Internal thread	G3/8 Internal thread	G3/8 Internal thread